


327401 - Recoat Stix

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** 327401 - Recoat Stix
Other means of identification:
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Acrylic paint. For professional users/industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Dercom BV
Platinawerf 24A
6641 TL Beuningen - Netherlands
Phone: +31 (0) 24 675 25 74
sds@dercom.nl
www.dercom.nl
- 1.4 Emergency telephone number:** +31 (0) 24 675 25 74 Mon-Fri 08:30 - 17:00 (CEST)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning

Hazard statements:
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
Precautionary statements:
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
P302+P352: IF ON SKIN: Wash with plenty of water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
Supplementary information:
Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).
Substances that contribute to the classification
octhilinone (ISO)
- 2.3 Other hazards:**
Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Non-applicable

3.2 Mixture:

Chemical description: Acrylic copolymer in aqueous solution

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | Concentration |
|---|---|---------------|
| CAS: 111-76-2 EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36-XXXX | 2-butoxyethanol⁽¹⁾ ATP ATP18 Regulation 1272/2008 Acute Tox. 3: H331; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Danger | 2,5 - <5 % |
| CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX | Dipropylene Glycol Methyl Ether⁽²⁾ Not classified Regulation 1272/2008 | <1 % |
| CAS: 112-34-5 EC: 203-961-6 Index: 603-096-00-8 REACH: 01-2119475104-44-XXXX | 2-(2-butoxyethoxy)ethanol⁽²⁾ ATP CLP00 Regulation 1272/2008 Eye Irrit. 2: H319 - Warning | <1 % |
| CAS: 2634-33-5 EC: 220-120-9 Index: 613-088-00-6 REACH: 01-2120761540-60-XXXX | 1,2-benzisothiazol-3(2H)-one⁽¹⁾ Self-classified Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger | <1 % |
| CAS: 26530-20-1 EC: 247-761-7 Index: 613-112-00-5 REACH: 01-2120768921-45-XXXX | octhilinone (ISO)⁽¹⁾ ATP ATP15 Regulation 1272/2008 Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1: H314; Skin Sens. 1A: H317; EUH071 - Danger | <1 % |
| CAS: 55965-84-9 EC: Non-applicable Index: 613-167-00-5 REACH: Non-applicable | Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)⁽¹⁾ ATP ATP13 Regulation 1272/2008 Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger | <1 % |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

| Identification | M-factor | |
|---|----------|---------|
| | Acute | Chronic |
| octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7 | 100 | 100 |
| Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable | 100 | 100 |

| Identification | Specific concentration limit |
|--|--|
| 1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9 | % (w/w) >=0,05: Skin Sens. 1 - H317 |
| octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7 | % (w/w) >=0,0015: Skin Sens. 1A - H317 |
| Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable | % (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317 |

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

| Identification | Acute toxicity | | Genus |
|---|-------------------|----------------|-------|
| | LD50 oral | LD50 dermal | |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | 1200 mg/kg (ATEi) | Non-applicable | Rat |
| | LC50 inhalation | 3 mg/L (ATEi) | |

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 10 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | Occupational exposure limits | | |
|--|------------------------------|--------|-------------------------|
| | IOELV (8h) | 20 ppm | 98 mg/m ³ |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | IOELV (STEL) | 50 ppm | 246 mg/m ³ |
| | IOELV (8h) | 50 ppm | 308 mg/m ³ |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | IOELV (STEL) | | |
| | IOELV (8h) | 10 ppm | 67,5 mg/m ³ |
| 2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6 | IOELV (STEL) | 15 ppm | 101,2 mg/m ³ |

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|---|------------|------------------------|-------------------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | 89 mg/kg | Non-applicable | 125 mg/kg | Non-applicable |
| | Inhalation | 1091 mg/m ³ | 246 mg/m ³ | 98 mg/m ³ | Non-applicable |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 283 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 308 mg/m ³ | Non-applicable |
| 2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 83 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 101,2 mg/m ³ | 67,5 mg/m ³ | 67,5 mg/m ³ |
| 1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 0,966 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 6,81 mg/m ³ | Non-applicable |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|---|------------|-----------------------|------------------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | Oral | Non-applicable | Non-applicable | 6,3 mg/kg | Non-applicable |
| | Dermal | 89 mg/kg | Non-applicable | 75 mg/kg | Non-applicable |
| | Inhalation | 426 mg/m ³ | 147 mg/m ³ | 59 mg/m ³ | Non-applicable |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | Oral | Non-applicable | Non-applicable | 36 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 121 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 37,2 mg/m ³ | Non-applicable |
| 2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6 | Oral | Non-applicable | Non-applicable | 5 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 50 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 60,7 mg/m ³ | 40,5 mg/m ³ | 40,5 mg/m ³ |
| 1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 0,345 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 1,2 mg/m ³ | Non-applicable |

PNEC:

| Identification | | | | |
|---|--------------|----------------|-------------------------|---------------|
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | STP | 463 mg/L | Fresh water | 8,8 mg/L |
| | Soil | 2,33 mg/kg | Marine water | 0,88 mg/L |
| | Intermittent | 26,4 mg/L | Sediment (Fresh water) | 34,6 mg/kg |
| | Oral | 0,02 g/kg | Sediment (Marine water) | 3,46 mg/kg |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | STP | 4168 mg/L | Fresh water | 19 mg/L |
| | Soil | 2,74 mg/kg | Marine water | 1,9 mg/L |
| | Intermittent | 190 mg/L | Sediment (Fresh water) | 70,2 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 7,02 mg/kg |
| 2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6 | STP | 200 mg/L | Fresh water | 1,1 mg/L |
| | Soil | 0,32 mg/kg | Marine water | 0,11 mg/L |
| | Intermittent | 11 mg/L | Sediment (Fresh water) | 4,4 mg/kg |
| | Oral | 0,056 g/kg | Sediment (Marine water) | 0,44 mg/kg |
| 1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9 | STP | 1,03 mg/L | Fresh water | 0,00403 mg/L |
| | Soil | 3 mg/kg | Marine water | 0,000403 mg/L |
| | Intermittent | 0,0011 mg/L | Sediment (Fresh water) | 0,0499 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,00499 mg/kg |
| octhlinone (ISO) CAS: 26530-20-1 EC: 247-761-7 | STP | Non-applicable | Fresh water | 0,0022 mg/L |
| | Soil | 0,0082 mg/kg | Marine water | 0,00022 mg/L |
| | Intermittent | 0,00122 mg/L | Sediment (Fresh water) | 0,0475 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,00475 mg/kg |

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|-----------------------------------|---|---------------------|--|
|  Mandatory respiratory tract protection | Filter mask for gases and vapours |  | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---------------------------------------|---|--------------|--|
|  Mandatory hand protection | Protective gloves against minor risks |  | | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018 |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|---|---------------------------------|---|
|  Mandatory face protection | Panoramic glasses against splash/projections. |  | EN 166:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|----------------------|---|-------------------|---|
| | Work clothing |  | | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994. |
| | Anti-slip work shoes |  | EN ISO 20347:2012 | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007 |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 2,68 % weight

327401 - Recoat Stix

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| | |
|---------------------------|-------------------------------------|
| V.O.C. density at 20 °C: | 27,75 kg/m ³ (27,75 g/L) |
| Average carbon number: | 6,08 |
| Average molecular weight: | 119,99 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|------------------|
| Physical state at 20 °C: | Liquid |
| Appearance: | Not available |
| Colour: | Not available |
| Odour: | Not available |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|-------------------------|
| Boiling point at atmospheric pressure: | 101 °C |
| Vapour pressure at 20 °C: | 2339 Pa |
| Vapour pressure at 50 °C: | 12322,96 Pa (12,32 kPa) |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|--|--------------------------|
| Density at 20 °C: | 1036,9 kg/m ³ |
| Relative density at 20 °C: | 1,037 |
| Dynamic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 40 °C: | Non-applicable * |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Non-applicable * |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |

Flammability:

| | |
|----------------------------|------------------------|
| Flash Point: | Non Flammable (>60 °C) |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 204 °C |
| Lower flammability limit: | Non-applicable * |
| Upper flammability limit: | Non-applicable * |

Particle characteristics:

| | |
|-----------------------------|----------------|
| Median equivalent diameter: | Non-applicable |
|-----------------------------|----------------|

9.2 Other information:

Information with regard to physical hazard classes:

| | |
|-----------------------|------------------|
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | |
|--|------------------|
| Corrosive to metals: | Non-applicable * |
| Heat of combustion: | Non-applicable * |
| Aerosols-total percentage (by mass) of flammable components: | Non-applicable * |
| Other safety characteristics: | |
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|----------------|----------------|
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: 2-butoxyethanol (3); propan-2-ol (3); 2,6-di-tert-butyl-p-cresol (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|--|-----------------|-------------------|--------|
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | LD50 oral | 1200 mg/kg (ATEi) | Rat |
| | LD50 dermal | 3000 mg/kg | Rabbit |
| | LC50 inhalation | 3 mg/L (ATEi) | |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | LD50 oral | >5000 mg/kg | Rat |
| | LD50 dermal | 9510 mg/kg | Rabbit |
| | LC50 inhalation | Non-applicable | |
| 1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9 | LD50 oral | 500 mg/kg | Rat |
| | LD50 dermal | Non-applicable | |
| | LC50 inhalation | Non-applicable | |
| octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7 | LD50 oral | 125 mg/kg | |
| | LD50 dermal | 311 mg/kg | |
| | LC50 inhalation | Non-applicable | |
| Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable | LD50 oral | 64 mg/kg | Rat |
| | LD50 dermal | 87,12 mg/kg | Rabbit |
| | LC50 inhalation | 0,33 mg/L (4 h) | Rat |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

| Identification | Concentration | Species | Genus |
|--|---------------------------|---------------------------------|------------|
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | LC50 1490 mg/L (96 h) | Lepomis macrochirus | Fish |
| | EC50 1815 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 911 mg/L (72 h) | Pseudokirchneriella subcapitata | Algae |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | LC50 10000 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 1919 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 Non-applicable | | |
| 2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6 | LC50 1300 mg/L (96 h) | Lepomis macrochirus | Fish |
| | EC50 2850 mg/L (24 h) | Daphnia magna | Crustacean |
| | EC50 53 mg/L (192 h) | Microcystis aeruginosa | Algae |
| 1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9 | LC50 2,2 mg/L (96 h) | Oncorhynchus mykiss | Fish |
| | EC50 3 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 0,067 mg/L (72 h) | Pseudokirchneriella subcapitata | Algae |
| octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7 | LC50 >0.1 - 1 mg/L (96 h) | | Fish |
| | EC50 >0.1 - 1 mg/L (48 h) | | Crustacean |
| | EC50 >0.1 - 1 mg/L (72 h) | | Algae |
| Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable | LC50 >0.1 - 1 mg/L (96 h) | | Fish |
| | EC50 >0.1 - 1 mg/L (48 h) | | Crustacean |
| | EC50 >0.1 - 1 mg/L (72 h) | | Algae |

Chronic toxicity:

| Identification | Concentration | Species | Genus |
|--|---------------------|---------------|------------|
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | NOEC 100 mg/L | Danio rerio | Fish |
| | NOEC 100 mg/L | Daphnia magna | Crustacean |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | NOEC Non-applicable | | |
| | NOEC 0,5 mg/L | Daphnia magna | Crustacean |

12.2 Persistence and degradability:

Substance-specific information:

| Identification | Degradability | | Biodegradability | |
|---|---------------|----------------|------------------|----------------|
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | BOD5 | 0,71 g O2/g | Concentration | 100 mg/L |
| | COD | 2,2 g O2/g | Period | 14 days |
| | BOD5/COD | 0,32 | % Biodegradable | 96 % |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | BOD5 | Non-applicable | Concentration | Non-applicable |
| | COD | 0 g O2/g | Period | 28 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 73 % |
| 2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6 | BOD5 | 0,25 g O2/g | Concentration | 100 mg/L |
| | COD | 2,08 g O2/g | Period | 28 days |
| | BOD5/COD | 0,12 | % Biodegradable | 92 % |
| 1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9 | BOD5 | Non-applicable | Concentration | 100 mg/L |
| | COD | Non-applicable | Period | 28 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 0 % |

12.3 Bioaccumulative potential:

Substance-specific information:

| Identification | Bioaccumulation potential | |
|---|---------------------------|------|
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | BCF | 3 |
| | Pow Log | 0.83 |
| | Potential | Low |

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix

SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Bioaccumulation potential | |
|---|---------------------------|-------|
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | BCF | 1 |
| | Pow Log | -0.06 |
| | Potential | Low |
| 2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6 | BCF | 0.46 |
| | Pow Log | 0.56 |
| | Potential | Low |
| 1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9 | BCF | 2 |
| | Pow Log | 1.45 |
| | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|---|-----------------------|----------------------|------------|---------------------------------|
| 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 | Koc | 8 | Henry | 1,621E-1 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | No |
| | Surface tension | 2,729E-2 N/m (25 °C) | Moist soil | Yes |
| 2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6 | Koc | 48 | Henry | 7,2E-9 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | No |
| | Surface tension | 3,395E-2 N/m (25 °C) | Moist soil | No |

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix**SECTION 15: REGULATORY INFORMATION (continued)**

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one, bronopol (INN), octhilinone (ISO).

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 11, 12, 13) ; octhilinone (ISO) (Product-type 6, 7, 8, 9, 10, 11, 13) ; Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ...):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -

327401 - Recoat Stix**SECTION 16: OTHER INFORMATION (continued)**

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.
Acute Tox. 2: H330 - Fatal if inhaled.
Acute Tox. 3: H301 - Toxic if swallowed.
Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.
Acute Tox. 3: H331 - Toxic if inhaled.
Acute Tox. 4: H302 - Harmful if swallowed.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Skin Corr. 1: H314 - Causes severe skin burns and eye damage.
Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Classification procedure:

Skin Sens. 1A: Calculation method
Aquatic Chronic 3: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -