This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

ercom COATING INNOVATIONS

385011 - Recoat Stix UV

1.1	Product identifier:	385011 - Recoat Stix UV
	Other means of identification:	
	Non-applicable	
1.2	Relevant identified uses of the s	substance or mixture and uses advised against:
	Relevant uses: Acrylic paint. For pro	fessional users/industrial user only.
	Uses advised against: All uses not sp	pecified in this section or in section 7.3
1.3	Details of the supplier of the saf	fety data sheet:
	Dercom BV Bijsterhuizen 2525 6604 LM Wijchen - Netherlands Phone: +31 (0) 24 675 25 74 sds@dercom.nl www.dercom.nl	
1.4	Emergency telephone number:	+31 (0) 24 675 25 74 Mon-Fri 08:30 - 17:00 (CEST)
SEC	TION 2: HAZARDS IDENTIFICAT	ION
2.1	Classification of the substance of	or mixture:
	CLP Regulation (EC) No 1272/2	008:
	The product is not classified as haza	ardous according to CLP Regulation (EC) No 1272/2008.
2.2	Label elements:	
	CLP Regulation (EC) No 1272/2	008:
	Hazard statements:	
	Non-applicable	
	Precautionary statements:	
	Non-applicable	
	Supplementary information:	
	EUH208: Contains 1,2-benzisothiazo	ol-3(2H)-one. May produce an allergic reaction.
2.3	EUH208: Contains 1,2-benzisothiazo EUH210: Safety data sheet available	ol-3(2H)-one. May produce an allergic reaction.
2.3	EUH208: Contains 1,2-benzisothiazo EUH210: Safety data sheet available Other hazards:	ol-3(2H)-one. May produce an allergic reaction. e on request.
2.3	EUH208: Contains 1,2-benzisothiazo EUH210: Safety data sheet available Other hazards: Product does not meet PBT/vPvB cri	ol-3(2H)-one. May produce an allergic reaction. e on request.
_	EUH208: Contains 1,2-benzisothiazo EUH210: Safety data sheet available Other hazards: Product does not meet PBT/vPvB cri Endocrine-disrupting properties: The	ol-3(2H)-one. May produce an allergic reaction. e on request. iteria e product does not meet the criteria.
-	EUH208: Contains 1,2-benzisothiazo EUH210: Safety data sheet available Other hazards: Product does not meet PBT/vPvB cri	ol-3(2H)-one. May produce an allergic reaction. e on request. iteria e product does not meet the criteria.
2.3 SEC 3.1	EUH208: Contains 1,2-benzisothiazo EUH210: Safety data sheet available Other hazards: Product does not meet PBT/vPvB cri Endocrine-disrupting properties: The	ol-3(2H)-one. May produce an allergic reaction. e on request. iteria e product does not meet the criteria.

3.2 Mixture:

Chemical description: Acrylic copolymer in aqueous solution

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
CAS: EC:	34590-94-8 252-104-2	Dipropylene Glycol M	ethyl Ether ⁽¹⁾ Not classified	
Index:	Non-applicable 01-2119450011-60- XXXX	Regulation 1272/2008		2,5 - <5 %
(1) Substance with a Union workplace exposure limit				

⁽¹⁾ Substance with a Union workplace exposure limit
 ⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

** Changes with regards to the previous version

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation



385011 - Recoat Stix UV

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

	Identification		Chemical name/Classification			
CAS: EC:	2634-33-5 220-120-9	1,2-benzisothiazol-3	(2H)-one ⁽²⁾	Self-classified		
Index:	613-088-00-6 01-2120761540-60- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Eye Dam. 1 H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	· ()	0,025 - <0,05 %	

(1) Substance with a Union workplace exposure limit

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	% (w/w) >=0,05: Skin Sens. 1 - H317

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.



385011 - Recoat Stix UV

SECTION 5: FIREFIGHTING MEASURES (continued)

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

- A.- Technical measures for storage
 - Minimum Temp.:10 °CMaximum Temp.:30 °CMaximum time:12 Months
- B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

385011 - Recoat Stix UV

SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Dipropylene Glycol Methyl Ether	IOELV (8h)	50 ppm	308 mg/m ³
CAS: 34590-94-8 EC: 252-104-2	IOELV (STEL)		

DNEL (Workers):

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Dipropylene Glycol Methyl Ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 34590-94-8	Dermal	Non-applicable	Non-applicable	283 mg/kg	Non-applicable	
EC: 252-104-2	Inhalation	Non-applicable	Non-applicable	308 mg/m ³	Non-applicable	
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,966 mg/kg	Non-applicable	
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	6,81 mg/m³	Non-applicable	

DNEL (General population):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Dipropylene Glycol Methyl Ether	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 34590-94-8	Dermal	Non-applicable	Non-applicable	121 mg/kg	Non-applicable
EC: 252-104-2	Inhalation	Non-applicable	Non-applicable	37,2 mg/m ³	Non-applicable
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,345 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	1,2 mg/m ³	Non-applicable

PNEC:

Identification				
Dipropylene Glycol Methyl Ether	STP	4168 mg/L	Fresh water	19 mg/L
CAS: 34590-94-8	Soil	2,74 mg/kg	Marine water	1,9 mg/L
EC: 252-104-2	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,02 mg/kg
1,2-benzisothiazol-3(2H)-one	STP	1,03 mg/L	Fresh water	0,00403 mg/L
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0,000403 mg/L
EC: 220-120-9	Intermittent	0,0011 mg/L	Sediment (Fresh water)	0,0499 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00499 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



385011 - Recoat Stix UV

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand	Protective gloves against minor risks	CAT		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend usin CE III gloves in line with standards EN 420:2004- A1:2010 and EN ISO 374-1:2016+A1:2018
protection	a mixture of several subs	tances the resi	stance of the glove mate	erial can not be calculated in advance with
	d has therefore to be che			
		Laballia a		Demonius
Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E Body protection				
Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. Fo periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulation in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CAT II	EN ISO 20347:2012	Replace before any evidence of deterioration. Fo periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulation in EN ISO 20345:2012 y EN 13832-1:2007
F Additional emerge	ency measures			
Emergency mea	asure St	andards	Emergency meas	sure Standards
Emergency sho	ISO 3864-1:20			ISO 3864-1:2011, ISO 3864-4:2011
Emergency sho	ISO 3864-1:20		1 Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011
Environmental exp In accordance with the	ISO 3864-1:20 ower controls: he community legislation product and its container.	11, ISO 3864-4:201	Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co	ISO 3864-1:20 ower controls: he community legislation product and its container.	11, ISO 3864-4:201 for the protectic For additional ir	Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co	ISO 3864-1:20 posure controls: the community legislation product and its container. products: tive 2010/75/EU, this product	11, ISO 3864-4:201 for the protectic For additional ir	Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with th spillage of both the p Volatile organic co With regard to Direct	ISO 3864-1:20 ower bosure controls: the community legislation product and its container. bosonation ive 2010/75/EU, this proc 3,02	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll	Eyewash statio on of the environment it iformation see subsectio owing characteristics:	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply):	ISO 3864-1:20 posure controls: the community legislation product and its container. mpounds: tive 2010/75/EU, this proc 3,02 20 °C: 31,32	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight	Eyewash statio on of the environment it iformation see subsectio owing characteristics:	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with th spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at	ISO 3864-1:20 posure controls: the community legislation or product and its container. mpounds: tive 2010/75/EU, this prod 3,02 20 °C: 31,32 number: 7,01	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight	Eyewash statio on of the environment it iformation see subsectio owing characteristics:	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with th spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon n Average molecula	ISO 3864-1:20 ower interview of the community legislation for orduct and its container. Interview 2010/75/EU, this procession of the community legislation for orduct and its container. Interview 2010/75/EU, this procession of the community legislation of the community legis	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol	Eyewash statio on of the environment it iformation see subsectio owing characteristics:	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon n Average molecula	ISO 3864-1:20 posure controls: the community legislation or product and its container. mpounds: tive 2010/75/EU, this prod 3,02 20 °C: 31,32 number: 7,01	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol	Eyewash statio on of the environment it oformation see subsection owing characteristics: g/L)	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon m Average molecula	ISO 3864-1:20 posure controls: the community legislation or product and its container. mpounds: tive 2010/75/EU, this prod 3,02 0 20 °C: 31,32 number: 7,01 ar weight: 148,0 AND CHEMICAL PROP	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol ERTIES cal properties	Eyewash statio on of the environment it oformation see subsection owing characteristics: g/L)	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon m Average molecula	ISO 3864-1:20 ower bosure controls: the community legislation product and its container. mpounds: tive 2010/75/EU, this prod 3,02 ° 20 °C: 31,32 number: 7,01 ar weight: 148,0 AND CHEMICAL PROP sic physical and chemi	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol ERTIES cal properties	Eyewash statio on of the environment it oformation see subsection owing characteristics: g/L)	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon in Average molecula TION 9: PHYSICAL / Information on base For complete information	ISO 3864-1:20 ower be community legislation orduct and its container. mpounds: tive 2010/75/EU, this proc 3,02 20 °C: 31,32 number: 7,01 ar weight: 148,0 AND CHEMICAL PROP sic physical and chemi ation see the product data	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol ERTIES cal properties	Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon in Average molecula TION 9: PHYSICAL / Information on base For complete information	ISO 3864-1:20 ower be community legislation orduct and its container. mpounds: tive 2010/75/EU, this proc 3,02 20 °C: 31,32 number: 7,01 ar weight: 148,0 AND CHEMICAL PROP sic physical and chemi ation see the product data	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol ERTIES cal properties asheet. Liquid	Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon m Average molecula TION 9: PHYSICAL A Information on base For complete information Appearance: Physical state at 20 °	ISO 3864-1:20 ower be community legislation orduct and its container. mpounds: tive 2010/75/EU, this proc 3,02 20 °C: 31,32 number: 7,01 ar weight: 148,0 AND CHEMICAL PROP sic physical and chemi ation see the product data	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol ERTIES cal properties asheet. Liquic Not a	Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon in Average molecula TION 9: PHYSICAL A Information on base For complete information Appearance: Physical state at 20 ° Appearance:	ISO 3864-1:20 ower be community legislation orduct and its container. mpounds: tive 2010/75/EU, this proc 3,02 20 °C: 31,32 number: 7,01 ar weight: 148,0 AND CHEMICAL PROP sic physical and chemi ation see the product data	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol ERTIES cal properties asheet. Liquid Not a Not a	Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011 is recommended to avoid environmental
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon in Average molecula TION 9: PHYSICAL A Information on base For complete informat Appearance: Physical state at 20 ° Appearance: Colour: Odour:	ISO 3864-1:20 ower be community legislation orduct and its container. mpounds: tive 2010/75/EU, this proc 3,02 20 °C: 31,32 number: 7,01 ar weight: 148,0 AND CHEMICAL PROP sic physical and chemi ation see the product data	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol ERTIES cal properties asheet. Liquid Not a Not a Not a	Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011
Environmental exp In accordance with the spillage of both the p Volatile organic co With regard to Direct V.O.C. (Supply): V.O.C. density at Average carbon in Average molecula TION 9: PHYSICAL A Information on base For complete informat Appearance: Physical state at 20 ° Appearance: Colour: Odour:	ISO 3864-1:20 ower Dosure controls: the community legislation oroduct and its container. the 2010/75/EU, this process a,02 20 20 20 20 20 20 20 20 20 20 20 20 2	11, ISO 3864-4:201 for the protectic For additional ir duct has the foll % weight kg/m ³ (31,32 9 g/mol ERTIES cal properties asheet. Liquid Not a Not a iding information p	Eyewash statio	ISO 3864-1:2011, ISO 3864-4:2011

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

385011 - Recoat Stix UV

Odour threshold: Non-applicable * Volatility: 102 °C Vapour pressure at 20 °C: 2340 Pa Vapour pressure at 20 °C: 102 327.01 Pa (12,33 kPa) Vapour of tessure at 20 °C: Non-applicable * Product description: 103 kg/m³ Relative density at 20 °C: 1038 kg/m³ Relative density at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Concentration: Non-applicable * Vapour density at 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Meting point/freezing point: Non-applicable * Paticle characteristics: Non-applicable * Quoer finamability linnit:	SEC	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	S (continued)
Boiling point at atmospheric pressure:102 °CVapour pressure at 0°C:2340 PaVapour pressure at 0°C:12327.01 Pa (12,33 kPa)Exportion rate at 0°C:Non-applicable *Density at 20 °C:1,038 kg/m³Relative density at 20 °C:1,038Dynamic viscosity at 20 °C:1,038Dynamic viscosity at 20 °C:Non-applicable *Concentration:Non-applicable *Concentration:Non-applicable *Concentration:Non-applicable *Prit:Non-applicable *Vapour density at 20 °C:Non-applicable *Solubility invest at 20 °C:Non-applicable *Density at 20 °C:Non-applicable *Solubility invest at 20 °C:Non-applicable *Prit:Non-applicable *Non-applicable *Non-applicable *Solubility invest at 20 °C:Non-applicable *Non-applicable *Non-applicable *Solubility invest at 20 °C:Non-applicable *Decomposition temperature:Non-applicable *Metting point/freezing point:76 °CFlammability:76 °CFlammability (solid, gas):Non-applicable *Autoignition temperature:Non-applicable *Upper flammability limit:204 °CUpper flammability limit:Non-applicable *Autoignition temperature:Non-applicable *Upper flammability limit:Non-applicable *Autoignition temperature:Non-applicable *Autoignition temperature:Non-applicable *Upper flammability l		Odour threshold:	Non-applicable *
Vapour pressure at 20 °C:2340 PaVapour pressure at 50 °C:12327,01 Pa (12,33 kPa)Evaporation rate at 20 °C:Non-applicable *Density at 20 °C:1,038 kg/m³Relative density at 20 °C:1,038Dynamic viscosity at 20 °C:Non-applicable *Kinematic viscosity at 20 °C:Non-applicable *Vapour density at 20 °C:Non-applicable *Solubility in water at 20 °C:Non-applicable *Solubility properties:Non-applicable *Solubility properties:Non-applicable *Autoigniton temperature:Non-applicable *Hammability coll (solid, gas):Non-applicable *Hammability imit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Hartin aquivalent diseters:Non-applicable *Explosive properties:Non-applicable *Oxidig properties:Non-applicable *Corrosive to metals:Non-applicable *Corrosive to metals:Non-applicable *Corrosive to metals:Non-applicable *Corrosive to metals:<		Volatility:	
Vapour pressure at 50 °C:12327,01 Pa (12,33 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1038 kg/m³Relative density at 20 °C:1,038Dynamic viscosity at 20 °C:Non-applicable *Kinematic viscosity at 20 °C:Non-applicable *Kinematic viscosity at 20 °C:Non-applicable *Concentration:Non-applicable *Orneut density at 20 °C:Non-applicable *Concentration:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *Solubility in water at 20 °C:Non-applicable *Solubility in water at 20 °C:Non-applicable *Decomposition temperature:Non-applicable *Meting point/freezing point:Non-applicable *Harmability:Non-applicable *Hamability (solid, gas):Non-applicable *Autoignition temperature:Non-applicable *Lower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Autoignition temperature:Non-applicable *Lower flammability limit:Non-applicable *Ordian quivalent diameter:Non-applicable *Corrosive to metals:Non-applicable *Corrosive to metals:Non-applicable *Autoignition temperature:Non-applicable *Autoignition temperature:Non-applicable *Corrosive to metals:Non-applicable *Corrosive to metals:Non-applicable *Corrosive to metal		Boiling point at atmospheric pressure:	102 °C
Evaporation rate at 20 °C: Non-applicable * Product description: 1038 kg/m³ Relative density at 20 °C: 1,038 Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Concentration: Non-applicable * PH: Non-applicable * Vapour density at 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility instruction Non-applicable * Meting point/freezing point: Yon-applicable * Harmability: Non-applicable * Upper fianmability limit: Yon * Upper fianmability limit: Non-applicable * Upper fianmability limit: Non-applicable * Upper fianmability limit:		Vapour pressure at 20 °C:	2340 Pa
Product description: 1038 kg/m³ Density at 20 °C: 1,038 Relative density at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: Non-applicable * Concentration: Non-applicable * Vajour density at 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility in properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: P6 °C Flammability: 76 °C Flammability (solid, gas): Non-applicable * Autoignition temperature: 204 °C Lower flammability limit: Non-applicable * Jupper flammability limit: Non-applicable * Autoignition temperature: Non-applicable * Lower flammability limit: Non-applicable * Oxidising properties: Non-applicable * Autoignition temperature: Non-applicable *		Vapour pressure at 50 °C:	12327,01 Pa (12,33 kPa)
Density at 20 °C:1.038 kg/m³Relative density at 20 °C:1.038Dynamic viscosity at 20 °C:Non-applicable *Kinematic viscosity at 20 °C:Non-applicable *Concentration:Non-applicable *PH:Non-applicable *Vapour density at 20 °C:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *Solubility in water at 20 °C:Non-applicable *Decomposition temperature:Non-applicable *Decomposition temperature:Non-applicable *Henting point/freezing point:Non-applicable *Hammability colid, gas):Non-applicable *Upper flammability limit:Non-applicable *U		Evaporation rate at 20 °C:	Non-applicable *
Relative density at 20 °C: 1,038 Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Concentration: Non-applicable * Concentration: Non-applicable * PH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Melting point/freezing point: Non-applicable * Partition temperature: Non-applicable * Hammability: Non-applicable * Upper flammability limit: Non-applicable * Oxidising properties: Non-applicable * Corro		Product description:	
Dynamic viscosity at 20 °C:Non-applicable *Kinematic viscosity at 40 °C:Non-applicable *Concentration:Non-applicable *Dynapur density at 20 °C:Non-applicable *Pit:Non-applicable *Solubility in water at 20 °C:Non-applicable *Solubility in water at 20 °C:Non-applicable *Solubility in properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Hammability:Non-applicable *Flammability:Non-applicable *Particle characteristics:Non-applicable *Lower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Particle characteristics:Non-applicable *Information with regard to physical hazard classerNon-applicable *Point formation:Non-applicable *Information:Non-applicable *Particle characteristics:Non-applicable *Point formation:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Acrosols-total percentage (by mass) of flammabileNon-applicable *Acrosols-total percentage (by mass) of flammableNon-applicable *Acrosols-total percentage (by mass) of flammabileNon-applicable *Acrosols-total percentage (by mass) of flammableNon-applicable *Acrosols-total percentage		Density at 20 °C:	1038 kg/m³
Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: Non-applicable * Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Metring point/freezing point: Non-applicable * Hammability: Non-applicable * Flammability (solid, gas): Non-applicable * Autoignition temperature: 204 °C Lower flammability limit: Non-applicable * Upper flammability limit: Non-applicable * Particle characteristics: Non-applicable * Upper flammability limit: Non-applicable * Volidsing properties: Non-applicable * Oxidising properties: Non-applicable * Corrosive to metals: Non-applicable * Oxidising properties: Non-applicable * Oxidising properties: Non-applicable * Corrosive to metals: <td< th=""><th></th><th>Relative density at 20 °C:</th><th>1,038</th></td<>		Relative density at 20 °C:	1,038
Kinematic viscosity at 40 °C: Non-applicable * Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable * Flammability: Non-applicable * Flammability: Non-applicable * Flammability: Non-applicable * Melting point/freezing point: Non-applicable * Autoignition temperature: 204 °C Lower flammability limit: Non-applicable * Median equivalent diameter: 204 °C Lower flammability limit: Non-applicable * Vapor flammability limit: Non-applicable * Vapor flammability limit: Non-applicable * Vapor flammability limit: Non-applicable * Oxidising properties: Non-applicable * Oxidising properties: Non-applicable * Oxidising properties: Non-applicable * Heat of combuston: Non-applicable *		Dynamic viscosity at 20 °C:	Non-applicable *
Concentration:Non-applicable *pH:Non-applicable *Vapour density at 20 °C:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *Solubility in water at 20 °C:Non-applicable *Decomposition temperature:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *HammabilityNon-applicable *Melting point/freezing point:Non-applicable *Hammability (solid, gas):Non-applicable *Autoignition temperature:204 °CLower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Uther safety characteristics:Non-applicable *		Kinematic viscosity at 20 °C:	Non-applicable *
pH:Non-applicable *Vapour density at 20 °C:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *Solubility in water at 20 °C:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Hammability:Non-applicable *Flammability (solid, gas):Non-applicable *Autoignition temperature:204 °CLower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Other information:Non-applicable *Particle characteristics:Non-applicable *Upper flammability limit:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Aerosols-total percentage (by mass) of flammableNon-applicable *Aerosols-total percentage (by mass) of flammableNon-applicable *Cornosive to metals:Non-applicable *Aerosols-total percentage (by mass) of flammableNon-applicable *Cornosive to metals:Non-applicable *Aerosols-total percentage (by mass) of flammableNon-applicable *Autor total percentage (by		Kinematic viscosity at 40 °C:	Non-applicable *
Vapour density at 20 °C:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *Solubility in water at 20 °C:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Flammability:Non-applicable *Flammability (solid, gas):Non-applicable *Autoignition temperature:204 °CLower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Decomposition temperature:204 °CLower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Decomposition temperature:Entertient (Comparition (Comparities)))Information:Information:Information:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Aerosols-total percentage (by mass) of flammabileNon-applicable *Other safety characteristics:Non-applicable *Outrage tension at 20 °C:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable		Concentration:	Non-applicable *
Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Meting point/freezing point: Non-applicable * Flammability: Flammability: Flammability: 76 °C Flammability (solid, gas): Non-applicable * Autoignition temperature: 204 °C Lower flammability limit: Non-applicable * Median equivalent diameter: Non-applicable * Median equivalent diameter: Non-applicable * Information: Non-applicable * Information: Non-applicable * Information: Non-applicable * Acrosols: total percentage to physical hazard classes: Non-applicable * Oxidising properties: Non-applicable * Aerosols: total percentage (by mass) of flammable Non-applicable * Where a fartion		pH:	Non-applicable *
Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Metting point/freezing point: Non-applicable * Flammability: Non-applicable * Flammability: Non-applicable * Flammability (solid, gas): Non-applicable * Autoignition temperature: 204 °C Lower flammability limit: Non-applicable * Upper flammability limit: Non-applicable * Upper flammability limit: Non-applicable * Median equivalent diameter: Non-applicable * Median equivalent diameter: Non-applicable * Particle characteristics: Non-applicable * Kedian equivalent diameter: Non-applicable * Oxidising properties: Non-applicable * Oxidising properties: Non-applicable * Oxidising properties: Non-applicable * Meta of combustion: Non-applicable * Heat of combustion: Non-applicable * Heat of combustion: Non-applicable * Corrosive to metals: Non-applicable * Metar of combustion: Non-applica		Vapour density at 20 °C:	Non-applicable *
Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Hammability:Non-applicable *Flash Point:76 °CFlammability (solid, gas):Non-applicable *Autoignition temperature:204 °CLower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Deter information:Non-applicable *Information with regard to physical hazard classerExplosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Non-applicable *Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *Refraction index:Non-applicable *		Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Melting point/freezing point:Non-applicable *Flammability:Flash Point:76 °CFlammability (solid, gas):Non-applicable *Autoignition temperature:204 °CLower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Deter information:Non-applicable *Information with regard to physical hazard classes:Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Chres safety characteristics:Non-applicable *Other safety characteristics:Non-applicable *Gurface tension at 20 °C:Non-applicable *Kefraction index:Non-applicable *		Solubility in water at 20 °C:	Non-applicable *
Melting point/freezing point:Non-applicable *Flammability:Flammability:Flash Point:76 °CFlammability (solid, gas):Non-applicable *Autoignition temperature:204 °CLower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Particle characteristics:Non-applicable *Median equivalent diameter:Non-applicable *Particle characteristics:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Heat of combustion:Non-applicable *Components:Non-applicable *Dther safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *Refraction index:Non-applicable *		Solubility properties:	Non-applicable *
Flammability: 76 °C Flammability (solid, gas): Non-applicable * Autoignition temperature: 204 °C Lower flammability limit: Non-applicable * Upper flammability limit: Non-applicable * Particle characteristics: Non-applicable * Median equivalent diameter: Non-applicable * Particle characteristics: Non-applicable * Median equivalent diameter: Non-applicable * Corrosive properties: Non-applicable * Corrosive to metals: Non-applicable * Heat of combustion: Non-applicable * Aerosols-total percentage (by mass) of flammable components: Non-applicable * Other safety characteristics: Non-applicable * Surface tension at 20 °C: Non-applicable * Refraction index: Non-applicable *		Decomposition temperature:	Non-applicable *
Flash Point:76 °CFlammability (solid, gas):Non-applicable *Autoignition temperature:204 °CLower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Particle characteristics:Non-applicable *Median equivalent diameter:Non-applicableParticle characteristics:Non-applicable *Median equivalent diameter:Non-applicable *Difformation:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		Melting point/freezing point:	Non-applicable *
Flammability (solid, gas): Non-applicable * Autoignition temperature: 204 °C Lower flammability limit: Non-applicable * Upper flammability limit: Non-applicable * Upper flammability limit: Non-applicable * Particle characteristics: Non-applicable * Particle characteristics: Non-applicable * Median equivalent diameter: Non-applicable * Other information: Non-applicable * Information with regard to physical hazard classes: Explosive properties: Oxidising properties: Non-applicable * Oxidising properties: Non-applicable * Corrosive to metals: Non-applicable * Heat of combustion: Non-applicable * Aerosols-total percentage (by mass) of flammable components: Non-applicable * Other safety characteristics: Von-applicable * Surface tension at 20 °C: Non-applicable * Refraction index: Non-applicable *		Flammability:	
Autoignition temperature:204 °CLower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Particle characteristics:Non-applicable *Median equivalent diameter:Non-applicable9.2Other information:Information with regard to physical hazard classes:Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Dther safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *Refraction index:Non-applicable *Outper safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable		Flash Point:	76 ºC
Lower flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Upper flammability limit:Non-applicable *Particle characteristics:Non-applicable *Median equivalent diameter:Non-applicable9.2Other information:Information with regard to physical hazard classerExplosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Heat of combustion:Non-applicable *Components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		Flammability (solid, gas):	
Upper flammability limit:Non-applicable *Particle characteristics:Non-applicable *Median equivalent diameter:Non-applicable9.2Other information:Funformation with regard to physical hazard classerExplosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Heat of combustion:Non-applicable *Other safety characteristics:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *			
Particle characteristics:Non-applicableMedian equivalent diameter:Non-applicable9.2Other information:Information with regard to physical hazard classes:Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		Lower flammability limit:	Non-applicable *
Median equivalent diameter:Non-applicable9.2Other information:Information with regard to physical hazard classerExplosive properties:Non-applicable *Oxidising properties:Non-applicable *Oxidising properties:Non-applicable *Heat of combustion:Non-applicable *Heat of combustion:Non-applicable *Other safety characteristics:Non-applicable *Outplace tension at 20 °C:Non-applicable *Refraction index:Non-applicable *			Non-applicable *
9.2Other information:Information with regard to physical hazard classes:Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		Particle characteristics:	
Information with regard to physical hazard classes:Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		Median equivalent diameter:	Non-applicable
Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *	9.2		
Oxidising properties:Non-applicable *Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		Information with regard to physical hazard clas	
Corrosive to metals:Non-applicable *Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		Explosive properties:	
Heat of combustion:Non-applicable *Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		Oxidising properties:	
Aerosols-total percentage (by mass) of flammable components:Non-applicable *Other safety characteristics:Non-applicable *Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		Corrosive to metals:	
components:Other safety characteristics:Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *			
Surface tension at 20 °C:Non-applicable *Refraction index:Non-applicable *		components:	Non-applicable *
Refraction index: Non-applicable *		-	Non applicable *
יואטר ופופאמות מעפ נס נחפ חמנערפ סו נחפ סרסטענר, חסר סרסאומווט וחוסידוזמנוסח סרסספרנץ סד ונג המצמרמג.			
		"Not relevant due to the nature of the product, not providing info	mauon property of its nazaros.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

385011 - Recoat Stix UV

SECTION 10: STABILITY AND REACTIVITY (continued)

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

10.5

Applicable for handling and storage at room temperature:

	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
5	Incompatible materials	:			

Avoid strong acids Not applicable Not applicable Not applicable Avoid alkalis or strong bases	Acids	Water	Oxidising materials	Combustible materials	Others
	Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

- IARC: 2,6-di-tert-butyl-p-cresol (3); propan-2-ol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



385011 - Recoat Stix UV

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Ac	Acute toxicity		
Dipropylene Glycol Methyl Ether	LD50 oral	>5000 mg/kg	Rat	
CAS: 34590-94-8	LD50 dermal	9510 mg/kg	Rabbit	
EC: 252-104-2	LC50 inhalation	Non-applicable		
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat	
CAS: 2634-33-5	LD50 dermal	Non-applicable		
EC: 220-120-9	LC50 inhalation	Non-applicable		

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Dipropylene Glycol Methyl Ether	LC50	10000 mg/L (96 h)	Pimephales promelas	Fish
CAS: 34590-94-8	EC50	1919 mg/L (48 h)	Daphnia magna	Crustacean
EC: 252-104-2	EC50	Non-applicable		
1,2-benzisothiazol-3(2H)-one	LC50	2,2 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 2634-33-5	B-5 EC50 3 mg/L (48 h) Daphnia magna		Crustacean	
EC: 220-120-9	EC50	0,067 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Dipropylene Glycol Methyl Ether	NOEC	Non-applicable		
CAS: 34590-94-8 EC: 252-104-2	NOEC	0,5 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Dipropylene Glycol Methyl Ether	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 34590-94-8	COD	0 g O2/g	Period	28 days
EC: 252-104-2	BOD5/COD	Non-applicable	% Biodegradable	73 %



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

385011 - Recoat Stix UV

	Identification	De	Degradability		Biodegradability		
	1,2-benzisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	100 mg/L		
	CAS: 2634-33-5	COD	Non-applicable	Period	28 days		
	EC: 220-120-9	BOD5/COD	Non-applicable	% Biodegradable	0 %		
12.3	Bioaccumulative potential:	ative potential:					
	Substance-specific information:						
	Identification			Bioaccumulation potential			
	Dipropylene Glycol Methyl Ether		BCF	1			
	CAS: 34590-94-8			Pow Log	-0.06		
	EC: 252-104-2			Potential	Low		
	1,2-benzisothiazol-3(2H)-one			BCF Pow Log	2		
	CAS: 2634-33-5				1.45		
	EC: 220-120-9			Potential	Low		
12.4							
	Not available						
12.5	5 Results of PBT and vPvB assessment:						
	Product does not meet PBT/vPvB criteria						
12.6	Endocrine disrupting properties:						
	Endocrine-disrupting properties: The proc	luct does not meet th	e criteria.				
12.7	Other adverse effects:						
	Not described						

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 12	waste paint and varnish other than those mentioned in 08 01 11	Non dangerous

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one, Pyridine-2-thiol 1-oxide, sodium salt.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

385011 - Recoat Stix UV

SECTION 15: REGULATORY INFORMATION (continued)

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

Removed substances

1,2-benzisothiazol-3(2H)-one (2634-33-5)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

Substances contained in EUH208:

Removed substances

1,2-benzisothiazol-3(2H)-one (2634-33-5)

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Classification procedure:

Non-applicable

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

ercom COATING INNOVATIONS

385011 - Recoat Stix UV

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer



The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.