

# RECOAT - FLOOR CLEANER

Article Number: 31150



— RECOAT —

## PRODUCT DESCRIPTION

The Recoat Floor Cleaner is an environmentally friendly, universal cleaning and degreasing agent designed for deep cleaning of a wide range of floor types and flooring materials.

## AREA OF APPLICATION

Various flooring materials and substrates; linoleum, PVC, concrete, washed-out gravel, terrazzo, etc.

Removes black heel marks and other contamination from linoleum and PVC floors. Deep cleans embedded dirt from porous floors such as concrete, washed-out gravel, natural stone and terrazzo.

## JOB DESCRIPTION

Remove loose dust/grit with a vacuum cleaner, floor mop or other dry cleaning method.

Pretreatment before coating:

Depending on the level of contamination the Recoat Floor Cleaner can be diluted from 1:5 (standard) for normal cleaning, to 1:2 (1 litre cleaner to 2 litres of water) for deep cleaning.

Apply the diluted Recoat Floor Cleaner on a section of the floor by spray or mop.

Leave the solution on the substrate for 3-5 minutes to solve the embedded contamination. Scrub the treated section with a polishing machine or auto scrubber equipped with a white or red pad and remove all the dissolved contamination. When the entire floor is cleaned like this make one more overall run with the auto scrubber holding only clean water in the tank making sure to remove all cleaning residues.

Note: keep the quantity of water used for cleaning to a minimum. Be aware of large openings/crevices in the floor. Do not allow excessive amounts of cleaning solution in to run in the openings/crevices .

Note: when using the Recoat Floor Cleaner in high concentrations allow 2-3 hours drying time before using the floor.

For regular floor cleaning:

Dilute Floor Cleaner 1:50 to 1:100



## TECHNICAL PROPERTIES

Base	Water and surface activator
VOC content	This product contains 4 g/L VOC. This product is suitable for indoor and outdoor use
Application by means of	Mop, Spray
Cleaning materials	Water
PH Value	11
Thinning	Water 1:5 for normal cleaning to 1:2 for deep cleaning
Transport	Temperature during storage, transport and application minimum 5° C and maximum 30°C at a relative humidity of Maximum 85%
Storage stability	Unopened a maximum of two years in case of dry cool and frost-free storage.

## **SAFETY**

All Recoat products comply with the REACH standard.

## **ENVIRONMENT**

The product contains very small quantities of solvent and is largely manufactured in accordance with the green chemistry method.

## **IMPORTANT INFORMATION**

Recoat products are for professional use only. Specified processing and drying times are highly dependent on the conditions under which the product is used. It is of great importance that the applicator has sufficient knowledge of the substrate to which a specific product is applied. His knowledge and expertise determine the final result. Therefore no rights can be derived from these guidelines.