

RECOAT - BONDING AGENT

Article Number: 31279



— RECOAT —

PRODUCT DESCRIPTION

Metal, mineral and ceramic surfaces require preparation before applying a high-quality coating system.

Recoat Bonding Agent is an adhesion enhancer for various substrates. It increases the bonding surface of the substrate.

AREA OF APPLICATION

Recoat Bonding Agent is ideally suited to improve adhesion on steel, stainless steel, aluminium, zinc, galvanised and mineral substrates and ceramics.

JOB DESCRIPTION

Dilute Recoat Bonding Agent standard 1:1 with water. Apply Recoat Bonding Agent evenly over the surface with a cleaning mop and then allow to dry.



TECHNICAL PROPERTIES

Base	Water-based adhesion promoter
Approximate specific density	0,97 KG/L
Output	Approx. 15 m ² - 20 m ² / liter
Colour	Colourless
Mix ratio	1 : 1
VOC content	0 g/L This product is suitable for indoor and outdoor use.
Application by means of	Mop, Sponge
Application	Wear gloves and ensure sufficient ventilation
Cleaning materials	Water
Transport	Temperature during storage, transport and application minimum 5° C and maximum 30°C at a relative humidity of Maximum 85%
Storage stability	Unopened a maximum of two years in case of dry cool and frost-free storage.

SELECTION AND PREPARATION OF THE SUBSTRATE

Depends on the condition of the substrate. No residue may remain after cleaning, rinsing is therefore very important. Any problems in most cases are the result of insufficient cleaning or the use of wrong materials. The Recoat warranty will cease to apply in all of these cases. The final result depends on the treatment and the condition of the substrate.

Recoat will not assume any responsibility for failures caused by insufficient cleaning or the use of wrong materials.

SAFETY

All Recoat products comply with the REACH standard. The user of this product must comply with health safety and health regulations environment. Safety data sheet can be found at www.recoat.eu

ENVIRONMENT

The product contains very small quantities of solvent and is largely manufactured in accordance with the green chemistry method.

IMPORTANT INFORMATION

Recoat products are for professional use only. Specified processing and drying times are highly dependent on the conditions under which the product is used. It is of great importance that the applicator has sufficient knowledge of the substrate to which a specific product is applied. His knowledge and expertise determine the final result. Therefore no rights can be derived from these guidelines.